



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town, Jiading District, Shanghai

ENKPF BALANCING VALVE

MAIN TECHNICAL PARAMETER

PN(MPa)	Test pressure(MPa)		Working pressure(MPa)		Working temperature	Applicable medium
	Shell strength	Sealing performance	P ₂₀	P ₁₂		
1.6	2.4	1.76	1.5	1.6	≤200℃	Water, steam

MATERIAL FOR MAIN PARTS

Name of parts	Body	Hand wheel	Stem Sealing	Yoke nut	Washer	Packing
Material	C.I. \ Bronze Bowl-shaped steel, Stainless steel	C.I. \ Bowl-shaped steel,	Stainless steel	bronze	Rubber asbestos plank	Inflation graphite

MAIN EXTERNAL AND CONNECTION DIMENSIONS

Type	PN (MPa)	DN (mm) ₁	Dimensions(mm)						
			L	D	D ₁	n-φd	H	H ₁	D ₀
KPF-16 Stop valves type	1.6	15	130	95	65	4-14	150	160	80
		20	150	105	75	4-14	160	170	80
		25	160	115	85	4-14	182	197	80
		32	180	135	100	4-18	192	207	90
		40	200	145	110	4-18	250	270	100
		50	230	160	125	4-18	320	340	120
		65	290	180	145	4-18	380	410	200
		80	310	195	160	8-18	413	448	200
		100	350	215	180	8-18	466	506	240
		125	400	245	210	8-18	540	595	240
		150	480	280	240	8-23	623	688	360