



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town,
Jiading District, Shanghai

SELF BALANCING VALVE ENZLF

MAIN TECHNICAL PARAMETERS

Model	PN(MPa)	Casing test pressure	Working temperature	Medium used
ZLF-16	1.6	2.4 MPa	0~100℃	Water oil etc. non-corrosive media

MAIN EXTERNAL AND CONNECTING DIMENSIONS

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350
L	110	110	115	160	200	215	230	275	290	310	350	430	520	635	670
D	95	105	115	135	145	160	180	195	215	245	280	335	405	460	520
D ₁	65	75	85	100	110	125	145	160	180	210	240	295	355	410	470
D ₂	45	55	65	78	85	100	120	135	155	185	210	265	320	375	435
H ₁	72	72	81	108	138	138	143	170	193	208	254	289	325	357	372
H ₂	70	70	74	91	147	147	154	189	211	227	260	303	367	430	495
Flow control range (m ³ /h)	0.1~1	0.1~1.5	0.2~2	0.5~4	1~6	2~10	3~15	5~25	10~35	15~50	30~80	40~180	100~300	150~1500	200~700