

SELF PRESSURE DIFFENTIAL CONTROL VALVE ENZYC

MAIN TECHNICAL PARAMETERS

Model	PN(MPa)	Casing test pressure	Control range of pressure differential	
			Fixed pressure differential type	Adjustable pressure differential type
ZYC-16	1.6	2.4 MPa	10KPa、20KPa、30KPa	10~30KPa

MAIN EXTERNAL AND CONNECTING DIMENSIONS

DN mm	Way of connecti on	L mm	D	D ₁	D ₂	H(mm)		Flow (m ³ /h)	Medium used	Medium temperat ure	Part material
						Fixed pressure differential type	Adjustable pressure differential type				
15	Thread	110	95	65	45	95	145	0.2-1	Water	0~100℃	Body, upper and lower bonnets: cast iron valve core: copper membrane: nylon reinforced rubber spring: stainless steel
20		110	105	75	55	110	150	0.3- 1.5			
25		115	115	85	65	130	165	0.5-2			
32	Flange	130	135	100	78	140	190	1-4			
40		200	145	110	85	190	340	1.5-6			
50		215	160	125	100	205	355	2-8			
65		230	180	145	120	240	390	3-12			
80		275	195	160	135	300	500	5-20			
100		290	215	180	155	350	550	10-30			
125		310	245	210	185	380	580	15-45			