



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318. Nanxiang Town,
Jiading District, Shanghai

BUTT-CLAMPED TURBINE-DRIVEN RUBBER-LINED BUTTERFLY VALVE END371X/J

MAIN EXTERNAL AND CONNECTION DIMENSIONS

DN (mm)	PN (MPa)	Connection dimensions(mm)				External dimensions (mm)			
		L	D	D1	Zφd	END371X/J			
						H ₀	A	B	
40	1.0/1.6	43	145	110	4-18	295	193	125	
50		43	165	125	4-18	306	193	125	
65		46	185	145	4-18	320	193	125	
80		46	200	160	4-18/8-18	345	193	125	
100		52	220	180	8-18	385	193	125	
125		56	250	210	8-18	410	193	125	
150		56	285	240	8-22	445	193	125	
200		60	340	295	8-22/12-22	570	283	125	
250		68	395/405	350/355	12-22	645	283	165	
300		78	445/460	400/410	12-22	740	334	175	
350		1.0	78	505	460	16-22	765	334	175
400			102	565	515	16-26	875	425	210
450	114		615	565	20-26	940	425	210	
500	127		670	620	20-26	995	425	210	
600	154		780	725	20-30	1130	425	210	
700	165		895	840	24-30	1475	620	320	
800	190		1015	950	24-33	1535	620	320	
900	203		1115	1050	28-33	1660	620	320	
1000	216		1230	1160	28-39	1760	620	320	
1200	254		1455	1380	32-39	1995	620	320	
1200	0.6/0.25	254	1400/1375	1340/1320	32-34/32-30	1995	620	320	
1400		279	1620/1575	1560/1620	36-34/36-30	2360	620	320	
1600		318	1820/1785	1760/1730	40-34/40-30	2525	780	450	
1800		356	2045/1985	1970/1930	44-41/44-30	2860	780	450	
2000		406	2265/2185	2180/2130	48-48/48-30	3250	920	570	