



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318. Nanxiang Town,
Jiading District, Shanghai

BUTT-CLAMPED PNEUMATIC THREE-CAM BUTTERFLY VALVE END671/3X/F/H

MAIN EXTERNAL AND CONNECTION DIMENSIONS

DN (mm)	PN (MPa)	L	D1	D	Z φ d	H	END671/3 Type		
							H ₀	L1	L2
50	1.0/1.6	43	125	100	4-18	112	400	245	72
65		46	145	120	4-18	115	420	245	72
80		49	160	135	4-18/8-18	120	438	245	72
10		56	180	155	8-18	140	524	355	62
125		64	210	185	8-18	165	570	355	62
150		70	240	210	8-23	180	635	355	62
200		71	295	265	8-23/12-23	210	690	250	170
250		76	350/355	320	12-23/12-25	245	765	250	170
300		83	400/410	370	12-23/12-25	285	890	450	220
350		92	460/470	433	16-23/16-25	315	954	450	220
400		105	515/525	485	16-25/16-30	335	1070	450	220
450		114	565/585	535/550	20-25/20-30	380	1140	650	280
500		127	620/650	590/610	20-25/20-34	415	1200	650	280
600		154	725/770	670/720	20-30/20-37	475	1380	850	380
700		165	840	805	24-30/24-37	555	1580	850	380
800		190	950	913	24-34/24-41	640	1760	1250	380
900		203	1050	1013	28-34/28-41	720	1915	1250	380
1000		246	1160/1170	1122	28-34/28-45	770	2100	1250	380
1200		254	1380/1390	1335	32-41/32-51	890	2520	1250	380
1400		279	1590	1525	36-48/36-51	980			
1600	318	1820	1750	40-54	1120				
1800	356	2020	1950	44-54	1260				
2000	406	2230	2150	46-54	1400				
50	2.5/4.0	43	125	100	4-18	112	400	245	72
65		46	145	120	8-18	115	420	245	72
80		49	160	135	8-18	120	438	355	92
100		56	190	160	8-23	140	528	355	92
125		64	220	190	8-27	165	575	250	170
150		70	250	220	8-27	180	640	250	170
200		71	310/320	285	12-27/12-30	210	700	450	220
250		76	370/385	345	12-30/12-34	245	775	450	220
300		83	430/450	410	16-30/16-34	285	900	450	220
350		92	490/510	470	16-30/16-39	315	955	650	280
400		102	550/588	538	16-39/16-41	335	1080	650	280
450		114	600/610	564	20-39/20-45	380	1150	650	280
500		127	660/670	616	20-39/20-45	415	1210	850	380
600		154	770/795	735	20-41/20-51	475	1390	850	380
700		165	875	840	24-45	555	1600	1250	380
800		190	990	960	24-51	640	1780	1250	380
900		203	1090	1030	28-51	720	1930	1250	380
1000		216	1210	1145	28-56	770	2120	1250	380