

SLUDGE-PREVENTING OBSTRUCTING VALVE ENHS41X

MAIN PERFORMANCE PARAMETERS

PN(MPa)	Seal test(water) MPa	Strength test(water) MPa	Working temperature	Medium
1.6	1.76	2.4	≤80℃	Clean-water

MAIN CONNECTION DIMENSIONS

DN mm	Way of installation	L(mm)	L(mm)	Tubular thread D(mm)	D ₁	With sludge drain H ₁ (mm)	H(mm)	Width (mm)	No of bolt hole n-φd(mm)
20	Pipe thread	260		1 ³ / ₄ "		130	65	208	
25		260		1"		140	80	210	
32		280		1 ¹ / ₄ "		180	90	215	
40		320		1 ¹ / ₂ "		270	150	235	
50		400		2"		280	160	250	
40	Flange	440	415	145	100	335	165	235	4-18
50		500	458	160	125	360	180	250	4-18
65		620	480	180	145	560	250	425	4-18
80		680	550	195	160	640	285	450	8-18
100		760	650	215	180	695	310	465	8-18
125		870	735	245	210	730	340	495	8-18
150		1030	790	280	240	780	390	695	8-23
200		1170	1000	335	295	895	445	730	12-23
250		1320	1185	405	355	980	530	750	12-25