



公司名称: 上海天阀贸易有限公司
 邮 件: sales@tianvalve.com
 地 址: 上海市嘉定区南翔镇翔乐路318号

Y TYPE FILTER

MAIN TECHNICAL PARAMETER

PN(MPa)	Shell test pressure (MPa)	Working pressure	Body material	Sieve material	Applicable medium
1.0	1.5	1.0	Casting pig	Stainless steel	Water Air Oil
1.6	2.4	1.6	Ductile iron carbon steel		
2.5	3.75	2.5	carbon steel		

MAIN EXTERNAL AND CONNECTION DIMENSIONS

DN mm	L		D			D ₁			b			Z-φd			H		H ₁	
	SG41 GL41	YSTF	PN 1.0	PN 1.6	PN 2.5	PN 1.0	PN 1.6	PN 2.5	PN 1.0	PN 1.6	PN 2.5	PN 1.0	PN 1.6	PN 2.5	SG41 GL41	YSTF	SG41 GL41	YSTF
15	140		95	95	95	65	65	65	14	14	14	4-14	4-14	4-14	73		103	
20	150		105	105	105	75	75	75	16	16	16	4-14	4-14	4-14	88		127	
25	160		115	115	115	85	85	85	16	16	16	4-14	4-14	4-14	93		137	
32	180		135	135	140	100	100	100	18	18	18	4-18	4-18	4-18	100		148	
40	220		145	145	150	110	110	110	18	18	18	4-18	4-18	4-18	115		168	
50	240	310	160	160	165	125	125	125	20	20	20	4-18	4-18	4-18	155	155	195	195
65	250	380	180	180	185	145	145	145	20	20	22	4-18	4-18	8-18	198	198	270	270
80	320	420	195	195	200	160	160	160	22	22	24	8-18	8-18	8-18	210	210	295	295
100	380	460	215	215	235	180	180	190	24	24	24	8-18	8-18	8-22	250	250	344	344
125	440	540	245	245	270	210	210	220	26	26	26	8-18	8-18	8-26	305	305	422	422
150	500	610	285	285	300	240	240	250	26	26	28	8-22	8-22	8-26	358	358	485	485
200	600	750	340	340	360	295	295	310	28	30	30	8-22	12-22	12-26	450	450	602	602
250	600	795	395	405	425	350	355	370	28	32	32	12-22	12-26	12-30	503	503	710	710
300	630	860	445	460	485	400	410	430	28	32	34	12-22	12-26	16-30	578	578	815	815
350	780	1025	500	520	555	460	470	490	30	36	35	16-22	16-26	16-33	598	598	844	844
400	850	1150	565	580	620	515	525	550	32	38	40	16-26	16-30	16-36	618	618	872	872
500	850		670	715	730	620	650	660	34	42	44	20-26	20-33	20-36	693		978	
600	1000		780	840	845	725	770	770	36	48	46	20-30	20-36	20-39	765		1080	