



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town,
Jiading District, Shanghai

FORGED STEEL WEDLING GLOBE VALVE

STANDARD MATERIAL SPECIFICATIONS (CLASS 150LB~800LB)

NO.	Part Name	CS to ASTM	AS to ASTM	SS to ASTM	
		Type A105	Type F22	Type F304(L)	Type F316(L)
1	Body	A105	A182 F22	A182 F304(L)	A182 F316(L)
2	Disc	A276 420	A276 304	A276 304(L)	A276 316(L)
3	Stem	A182 F6	A182 F304	A182 F304(L)	A182 F316(L)
4	Gasket	Corrugated SS + graphite		SS + PTFE	
5	Bonnet	A105	A276 304	A276 304(L)	A276 316(L)
6	Bonnet Bolt	A193 B7	A193 B16	A193 B8	A193 B8M
7	Pin	A276 420		A276 304	
8	Gland	A276 410		A182 F304(L)	A182 F316(L)
9	Gland Eyebolt	A193 B7	A193 B16	A193 B8	A193 B8M
10	Gland Flange	A216 WCB		A351 CF8	
11	Gland Nut	A194 2H	A194 4	A194 8	A194 8M
12	Yoke Nut	A276 410			
13	H.W. Nut	A194 2H	A194 4	A194 8	A194 8M
14	Nameplate	SS			
15	Hand wheel	A197			
16	Stem Packing	Flexible Graphite		PTFE	
	Suitable Medium	W.O.G. etc	W.O.G. etc	HNO ₃ CH ₃ OOH etc	
	Suitable Temperature	-29℃~425℃	-29℃~550℃	-29℃~180℃	

Note: Other materials are available upon request.

DIMENSIONS (MM) AND WEIGHTS (KG)

NPS	Reduced	3/8	1/2	3/4	1	1-1/4	1-1/2	2	
	Full		3/8	1/2	3/4	1	1-1/4	1-1/2	2
L		79	79	92	111	120	152	172	200
H(OPEN)		166	166	171	207	240	258	330	355
W		100	100	100	125	160	160	180	200
Weights	Bolted	1.9	1.9	2.1	3.5	6.0	7.5	11.4	14.6
	Welded	1.7	1.7	1.9	3.3	5.2	6.8	10.6	13.8

STANDARD MATERIAL SPECIFICATIONS (CLASS 900LB~1500LB)

NO.	Part Name	CS to ASTM	AS to ASTM	SS to ASTM	
		Type A105	Type F22	Type F304(L)	Type F316(L)
1	Body	A105	A182 F22	A182 F304(L)	A182 F316(L)
2	Disc	A276 420	A276 304	A276 304(L)	A276 316(L)
3	Stem	A182 F6	A182 F304	A182 F304(L)	A182 F316(L)
4	Gasket	Corrugated SS + graphite		SS + PTFE	
5	Bonnet	A105	A276 304	A276 304(L)	A276 316(L)
6	Bonnet Bolt	A193 B7	A193 B16	A193 B8	A193 B8M



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town,
Jiading District, Shanghai

7	Pin	A276 420		A276 304	
8	Gland	A276 410		A182 F304(L)	A182 F316(L)
9	Gland Eyebolt	A193 B7	A193 B16	A193 B8	A193 B8M
10	Gland Flange	A216 WCB		A351 CF8	
11	Gland Nut	A194 2H	A194 4	A194 8	A194 8M
12	Yoke Nut	A276 410			
13	H.W. Nut	A194 2H	A194 4	A194 8	A194 8M
14	Nameplate	SS			
15	Hand wheel	A197			
16	Stem Packing	Flexible Graphite		PTFE	
	Suitable Medium	W.O.G. etc	W.O.G. etc	HNO ₃ ,CH ₃ OOH etc	
	Suitable Temperature	-29°C~425°C	-29°C~550°C	-29°C~180°C	

Note: Other materials are available upon request.

DIMENSIONS (MM) AND WEIGHTS (KG)

NPS	Reduced.	3/8	1/2	3/4	1	1-1/4	1-1/2	2	
	Full		3/8	1/2	3/4	1	1-1/4	1-1/2	2
L		92	111	111	120	152	172	200	220
H(OPEN)		171	207	207	240	258	330	355	370
W		100	125	125	160	160	180	200	240
Weights	Bolted	2.2	3.7	3.6	6.8	7.6	11.6	15.0	21.9
	Welded	2.0	3.4	3.3	6.0	5.6	10.3	14.2	18.0