

ECCENTRICITY PLUG VALVE

MAIN PART'S MATERIALS

NO	Part name	Material
1	Body	ASTM A216-WCB ASTM A351-CF8,CF8M,CF3,CF3M
2	Plug	ASTM A216-WCB ASTM A351-CF8,CF8M,CF3,CF3M
3	Seat	Stainless steel, Nickel, Resin
4	O-ring	EPDM,NBR
5	Bearing	Self-lubricated material
6	Bonnet	ASTM A216-WCB ASTM A351-CF8,CF8M,CF3,CF3M
7	V-ring	EPDM,NBR
8	Pressing plate	ASTM A216-WCB ASTM A351-CF8,CF8M,CF3,CF3M

SEHEMATIC DIAGRAM OF INSTALLATION

Model		X47-150LB														
Pressure		150LB														
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350
	in	1/2	3/4	1	1 ¹ / ₄	1 ¹ / ₂	2	2 ¹ / ₂	3	4	5	6	8	10	12	14
L-RF		108	117	127	140	165	178	190	203	229	254	267	292	330	356	381
L-BW		152	178	203	216	229	267	305	330	356	381	394	457	533	610	686
H		59	63	75	95	107	142	152	178	252	272	342	398	495	580	625
W		400	400	500	500	600	600	820	820	300	300	320	320	350	380	380
Weight(kg)		10	12	14	17	19	21	29	33	48	75	98	125	171	230	370

Model		X47-300LB														
Pressure		300LB														
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350
	in	1/2	3/4	1	1 ¹ / ₄	1 ¹ / ₂	2	2 ¹ / ₂	3	4	5	6	8	10	12	14
L-RF		140	152	165	178	190	216	241	283	305	381	403	419	457	502	762
L-BW		152	178	203	216	229	267	305	330	356	381	457	521	559	635	762
H		59	63	75	95	107	142	152	178	252	272	342	398	495	580	625
W		400	400	500	600	600	820	1000	1000	300	300	320	320	350	380	380
Weight(kg)		12	14	16	19	21	24	31	36	61	86	130	190	255	380	560

Model		X47-600LB														
Pressure		600LB														
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350
	in	1/2	3/4	1	1 ¹ / ₄	1 ¹ / ₂	2	2 ¹ / ₂	3	4	5	6	8	10	12	14
L-RF,BW		165	190	216	229	241	292	330	356	432	508	559	660	787	838	889
H		59	63	75	95	107	142	152	178	252	272	342	398	495	580	625
W		400	400	500	500	600	600	820	820	300	300	320	320	350	380	380
Weight(kg)		14	16	18	20	24	29	35	47	91	129	210	320	660	920	1250



公司名称: 上海天阀贸易有限公司
 邮 件: sales@tianvalve.com
 地 址: 上海市嘉定区南翔镇翔乐路318号

Model		X47-900LB														
Pressure		900LB														
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350
	in	1/2	3/4	1	1 ¹ / ₄	1 ¹ / ₂	2	2 ¹ / ₂	3	4	5	6	8	10	12	14
L-RF,BW		229	229	254	279	305	368	419	381	457	559	610	737	939	965	1029
H		59	63	75	95	107	142	152	178	252	272	342	398	495	580	625
W		400	400	500	600	600	820	1000	1000	300	300	320	320	350	380	380
Weight(kg)		17	29	21	24	30	37	44	65	110	160	255	380	810	1050	1460

Note: 4" or above with worm gear