



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town,  
Jiading District, Shanghai

## DIRECTLY ACTING PRESSURE REDUCING VALVE YZ11X

### MAIN TECHNICAL PARAMETERS

| Type                                | Model                   | PN(MPa)  | DN(mm) | Way of connection | Body material | Outlet pressure (MPa)    | Working temperature |
|-------------------------------------|-------------------------|----------|--------|-------------------|---------------|--------------------------|---------------------|
| Branch-pipe pressure reducing valve | YZ11X-16T,<br>YZ11X-25T | 1.6, 2.5 | 15~50  | Inner thread      | Bronze        | 0.05~0.6<br>(adjustable) | 0~80℃               |
|                                     | Stainless steel         |          |        |                   |               |                          |                     |

### MAIN EXTERNAL DIMENSIONS

| DN |       | Dimensions(mm) |     |      |    | Weight (Kg) |
|----|-------|----------------|-----|------|----|-------------|
| mm | In    | A              | B   | C    | φG |             |
| 15 | 1/2   | 31             | 60  | 76.5 | 59 | 1.2         |
| 20 | 3/4   | 31             | 75  | 76.5 | 73 | 1.2         |
| 25 | 1     | 36             | 88  | 85   | 81 | 1.4         |
| 32 | 1 1/4 | 42             | 93  | 98   | 81 | 1.5         |
| 40 | 1 1/2 | 45             | 98  | 102  | 85 | 2           |
| 50 | 2     | 54             | 130 | 117  | 98 | 2.65        |