



## A48C Type Pound-grade full lift spring loaded safety valve

### Main Property and specification

Normal Pressure	PN	150	300	600
Body strength	Ps (MPa)	3.0	7.5	15
Set pressure	Pk (MPa)	0.1~2	1.6~5	3.2~10
Seal pressure	Pm	90%Pk		
Reseating pressure	Ph	≥90%Pk		
Relieving pressure	Pp	≤1.1Pk		
Lift	H (mm)	≥1/4 do		
Appropriate temperature		≤350℃		
Appropriate medium		Steam		

### Code of throat diameter

Code	Diameter	Code	Diameter
D	10	L	50
E	13	M	55
F	16	N	60
G	20.5	P	72
H	26	Q	96
J	33	R	115
K	40	T	148

### Main Dimension

A48C150																	
Normal Diameter DN (in)	Dimension (mm)																
	do	D	D1	D2	b	t	z-φ d	DN'	D'	D1'	D2'	b'	t'	z-φ d'	L	L1	H
1/2" × 3/4"	D	89	60.5	35	12	6	4-15	20	98	70	43	14	1.6	4-15	90	90	290
3/4" × 1"	D	98	70	43	14	6	4-15	25	108	79.5	51	15	1.6	4-15	96	92	310
1" × 1 1/2"	D	108	79.5	51	15	7	4-15	40	127	98.5	73	18	1.6	4-15	115	105	320
1" × 2"	D	108	79.5	51	15	7	4-15	50	152	120.5	92	18	1.6	4-19	115	105	320
1 1/2" × 2"	G	127	98.5	73	18	6	4-15	50	152	120.5	92	18	1.6	4-19	121	124	350
1 1/2" × 2 1/2"	G	127	98.5	73	18	6	4-15	65	178	139.5	105	20	1.6	4-19	121	124	360
1 1/2" × 3"	G	127	98.5	73	18	6	4-15	80	190	152.5	127	22	1.6	4-19	124	130	360
2" × 2 1/2"	H	152	120.5	92	18	6	4-19	65	178	139.5	105	20	1.6	4-19	124	130	380
2" × 3"	J	152	120.5	92	18	6	4-19	80	190	152.5	127	22	1.6	4-19	124	130	380
2 1/2" × 4"	J	178	139.5	105	20	7	4-19	100	229	190.5	157	24	1.6	8-19	143	137	380
3" × 4"	L	190	152.5	127	22	10	4-19	100	229	190.5	157	24	1.6	8-19	162	156	480
4" × 6"	N	229	190.5	157	24	12	8-19	150	279	241.5	216	26	1.6	8-22	229	181	540
6" × 8"	P	279	241.5	216	26	10	8-22	200	343	298.5	270	29	1.6	8-22	241	240	760
8" × 10"	R	343	298.5	270	29	10	8-22	250	406	362	324	31	1.6	12-25	279	276	830
12" × 14"	T	483	432	381	32	10	12-25	350	533	476	413	35	1.6	12-28	370	360	890



A48C300																	
Normal Diameter DN (in)	Dimension (mm)																
	do	D	D1	D2	b	t	z-φ d	DN'	D'	D1'	D2'	b'	t'	z-φ d'	L	L1	H
12" × 3/4"	D	95	66.5	35	15	6	4-15	20	98	70	43	14	1.6	4-15	90	90	290
3/4" × 1"	D	117	82.5	43	16	10	4-19	25	105	79.5	51	15	1.6	4-15	96	92	310
1" × 1 1/2"	D	124	90	51	18	7	4-19	40	127	98.5	73	18	1.6	4-15	115	105	320
1" × 2"	D	124	90	51	18	6	4-19	50	152	120.5	92	18	1.6	4-19	115	105	320
1 1/2" × 2"	F	156	114.5	73	20	6	4-22	50	152	120.5	92	18	1.6	4-19	121	124	350
1 1/2" × 2 1/2"	F	156	114.5	73	20	9	4-22	65	178	139.5	105	20	1.6	4-19	121	124	360
1 1/2" × 3"	F	156	114.5	73	20	6	4-22	80	190	152.5	127	22	1.6	4-19	124	130	360
2" × 2 1/2"	H	165	127	92	22	6	8-19	65	178	139.5	105	20	1.6	4-19	124	130	380
2" × 3"	H	165	127	92	22	6	8-19	80	190	152.5	127	22	1.6	4-19	124	130	380
2 1/2" × 4"	J	190	149.5	105	24	7	8-22	100	229	190.5	157	24	1.6	8-19	143	137	380
3" × 4"	L	210	168	127	28	10	8-22	100	229	190.5	157	24	1.6	8-19	162	156	480
4" × 6"	N	254	200	157	32	12	8-22	150	279	241.5	216	26	1.6	8-22	229	181	540
6" × 8"	P	318	270	216	38	10	12-22	200	343	298.5	270	29	1.6	8-22	241	240	760
8" × 10"	R	381	330	270	42	10	12-25	250	406	362	324	31	1.6	12-25	279	276	830

Remark: 150Lb for outlet flange

A48C600																	
Normal Diameter DN (in)	Dimension (mm)																
	do	D	D1	D2	b	t	z-φ d	DN'	D'	D1'	D2'	b'	t'	z-φ d'	L	L1	H
3/4" × 1"	D	117	82.5	43	16	10	4-19	25	108	79.5	51	15	1.6	4-15	96	92	310
1" × 2"	D	124	90	51	19	6	4-19	50	152	120.5	92	18	1.6	4-19	115	105	320
1 1/2" × 2"	F	156	114.5	73	22	10	4-22	50	152	120.5	92	18	1.6	4-19	152	124	360
1 1/2" × 2 1/2"	F	156	114.5	73	22	9	4-22	65	178	139.5	105	20	1.6	4-19	152	214	380
1 1/2" × 3"	F	156	114.5	73	22	6	4-22	80	190	152.5	127	22	1.6	4-19	152	124	380
2" × 2 1/2"	H	165	127	92	26	6	8-19	65	178	139.5	105	20	1.6	4-19	162	154	410
2" × 3"	H	165	127	92	26	6	8-19	80	190	152.5	127	22	1.6	4-19	162	154	410
2 1/2" × 4"	K	190	149.5	105	29	7	8-22	100	229	190.5	157	24	1.6	8-19	143	165	410
3" × 4"	K	210	168	127	32	10	8-22	100	229	190.5	157	24	1.6	8-19	162	155	480
4" × 6"	N	273	215.9	157	38	12	8-25	150	279	241.5	216	26	1.6	8-22	210	200	540
6" × 8"	P	292	292	216	46	10	12-28	200	343	298.5	270	29	1.6	8-22	241	240	760

Remark: 150Lb for outlet flange