



Shanghai Tianfa Trading Co., Ltd.

E-mail: sales@tianvalve.com

Address: Road318, Nanxiang Town,
Jiading District, Shanghai

Closed spring loaded low lift type-high pressure safety valve

Dimensions (mm)

Type	DN	do	d	M	D	K	Z-φ d	b	d ₁	M ₁	D ₁	K ₁	Z ₁ -φ d ₁	b ₁	L	L ₁	≈H
A41Y-160	15	8	20	M24×2	95	60	3-18	20	/	M33×2	36	/	/	/	50	80	85
	20	10	25	M27×2	95	60	3-18	20	/	M33×2	48	/	/	/	50	80	85
	25	12	28	M33×2	105	68	3-18	20	/	M33×2	48	/	/	/	50	80	85
A41Y-160	10	8	18	M24×2	95	60	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	15	8	20	M24×2	95	60	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	20	10	27	M33×2	105	68	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	25	12	28	M42×2	105	68	3-18	20	50	M64×3	165	115	6-26	32	130	135	285
	32	12.14.16	37	M52×2	115	80	4-18	22	50	M64×3	165	115	6-26	32	130	135	285
	40	20	47	M64×2	165	115	6-26	28	65	M80×3	200	145	6-29	40	165	165	350
	50	25	58	M26×2	165	115	6-26	32	80	M100×3	225	170	6-33	80	165	165	380
A41Y-320	10	8	18	M24×2	95	60	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	15	8	27	M33×2	105	68	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	20	10	30	M36×2	110	75	3-18	20	29	M42×2	115	80	4-18	22	95	100	261
	25	12	35	M42×2	115	80	4-18	22	50	M64×3	165	115	6-26	32	130	135	285
	32	12.14.16	41	M48×2	135	95	4-22	25	50	M64×3	165	115	6-26	32	130	135	285
	40	20	58	M64×3	165	115	6-26	32	65	M80×3	200	145	6-29	40	165	115	350
	50	25	70	M80×3	200	145	6-29	40	80	M100×3	225	170	6-33	50	165	165	380